



TIGER^{LT}

Low cost VOC detection with market leading accuracy.



The leading technology of TIGER LT provides the most accurate, reliable detection of VOCs giving the right results and maximises field time.

Best available photoionisation detection (PID) sensor

- PID independently verified as best performing on the market
- Accurate results across all environments from 0.1 - 5000 ppm
- Patented humidity resistance to 99% RH - no compensation needed
- Anti-contamination design minimises drift and extends run time
- Fastest 2 second response time and rapid clear down

Minimise downtime

- Anti-contamination design reduces calibration frequency
- Li-ion battery for up to 24 hours continuous operation
- 6.5 hours battery charge time maximises uptime
- Batteries field replaceable, even in explosive environments
- Filters and lamps replaceable in minutes
- Simple icon driven menu requires minimal user training

Ease of use

- User selectable response factors for direct concentration readout
- Intuitive, easy to use software
- Large clear keypad for easy operation when wearing gloves
- Ergonomic design allows simple one handed operation
- Large, clear visual display
- Torch and back-lit keypad for low light conditions
- Push-to-log data logging, 128 zones, 80,000 points
- Designed for easy service

Safety

- 95 dBA, bright LED and vibration alarms alert you to gases present
- Intrinsically safe; meets ATEX, IECEx, UL and CSA standards

Low cost

- Entry level VOC detector with all the essential functions
- Inexpensive consumables and parts for low cost operation

Independently verified as best performing PID technology



The leading technology of the TIGER LT makes it the most advanced, low-cost handheld VOC detector on the market giving you the most accurate, reliable results you can count on, every time. Whether deciding to wear PPE or checking head space for compliance TIGER LT gives confidence that the right decision will be made in all environments, humid or dusty.

This variant of the hugely popular TIGER VOC detector is low on cost but high on performance. Its revolutionary, patented PID sensor technology with humidity resistance and anti-contamination design provide market leading accuracy and run time. Combined with 24 hour battery life, these features maximise field time by minimising erroneous readings in high humidity and drift in harsh environments.

The world's leading PID manufacturer, ION Science's PID sensor technology has also received independent verification as the best performing on the market for its speed of response, accuracy and linearity.

TIGER LT accurately detects gases from 0.1 to 5,000 ppm, has the fastest response time on the market of just 2 seconds, and is as quick to clear down. Its push-to-log data logging stores up to 80,000 data points in up to 128 user selectable zones.

The instrument has been designed with the user in mind for ease of use and servicing. Batteries can be replaced in potentially explosive environments due to the innovative Intrinsically Safe design. Low cost filters and lamps can be easily changed in minutes, minimising instrument downtime. Fast battery charging allows the instrument to be fully charged in just six hours.

TIGER LT offers simple, one handed operation even when wearing multiple pairs of thick gloves. Its rugged design and protective, removable rubber boot withstand harsh environmental conditions.

The large, clear back-lit display allows for easy viewing in any light condition. An integrated torch is designed for directing the instrument's probe into dimly lit areas. The illuminated keypad activates when light is low.

TIGER LT is a ground breaking, low cost entry level PID with all the essential functions you need for VOC detection. The instrument has the lowest running costs on the market with inexpensive disposable parts, lamps and filters.

Extend your instrument warranty

Warranty can be extended from one to two years if the instrument is registered online within one month of purchase. Visit www.ionscience.com/instrument-registration

Applications include

- Environmental monitoring • Soil contamination • VOCs in landfill • IAQ
- Health & Safety • Confined space entry • First Response • Wing tank entry
- VOC leak detection • Fumigation gases • Fugitive emissions • Medical gases

Accessories

An extensive range of accessories is also available. For more information visit: www.ionscience.com/tigerlt

Distributed by:



DUOTEC A/S
 Herstedøstervej 19 · 2600 Glostrup
 Tlf. 4345 9188 · Fax 4343 2330
 e-mail: info@duotec.dk
www.duotec.dk

TECHNICAL SPECIFICATIONS	
MINIMUM RESOLUTION *	0.1 ppm
MAXIMUM READING	5,000 ppm
RESPONSE TIME	T90 < 2 seconds
ACCURACY *	± 5% display reading ± one digit
LINEARITY *	± 5% display reading ± one digit
INTRINSICALLY SAFE APPROVALS	
Ⓢ II 1G Ex ia IIC T4 Ga Tamb = - 15 OC ≤ Ta ≤ +45 OC (with lithium ion battery pack) Tamb = - 15 OC ≤ Ta ≤ +40 OC (with alkaline battery pack) ITS09ATEX26890X IECEx ITS 10.0036X 3193491 conforms to UL Std. 913, 61010-1 & Certified to CAN/CSA Std. C22.2 No. 61010-1	
BATTERY LIFE	Li-ion: life up to 24 hours continual use
LAMPS	10.6 eV Krypton PID lamp (standard.) 10.0 eV and 11.7 eV lamps available
DATA LOGGING *	Push-to-log, 128 zones, 80,000 data points
CALIBRATION	Standard calibration 100 ppm isobutylene Custom calibration capability
ALARM	Flashing LED and 95 dBA at 300mm (12") audible sounder Selectable vibrating alarm
FLOW RATE	Flashing LED and 95 dBA at 300mm (12") audible sounder Selectable vibrating alarm
TEMPERATURE	Operating: -20 to 60 OC, -4 to 140 OF (non-Intrinsically Safe) Humidity: 0-99% RH (non condensing)
PROTECTION	Designed to IP65 (heavy rain) Ⓢ 1180 EMC tested to EN61326-1:2006, EN50270:2006 & CFR 47:2008 Class A
WEIGHT & DIMENSIONS	Instrument without probe Width: 340 x Height: 90 x Depth: 60 mm (13.4 x 3.6 x 2.4") Instrument weight 0.72 kg (1.56lb)

All specifications are against isobutylene calibration at 20 oC, 90% RH and up to 3000 ppm unless otherwise stated. *Gas dependent.

"The Tiger has impressed me with its reliability in humid environments. It's a nice size instrument, easy to use and is an easy piece of equipment to calibrate. It is an extremely good product, and the correspondence between Ion Science and myself has been prompt and precise."

Jeremy Kinman, Hydrogeologist, Arbury Environmental Engineering

Manufactured by:

Ion Science Ltd
 The Way, Fowlmere,
 Cambs, SG8 7UJ, UK
 T: +44 (0) 1763 208 503
 E: info@ionscience.com
www.ionscience.com



TIGER LT V1.1 This publication is not intended to form the basis of a contract and specifications can change without notice.